

# GLOBAL AQ AUTO CRACK BASE 9110



Global AQ Auto Crack Base 9110 is a two-layer printing system designed to create a unique auto-cracking effect on textiles. The first layer consists of a base formulated with dyes, specifically developed to achieve the desired cracking pattern on the fabric. The second layer, Global AQ Auto Crack White 9111, enhances the visual impact by providing contrast and definition to the cracks.

This innovative printing system delivers an excellent cracking effect with superior wash durability, ensuring long-lasting designs. The size of the cracks can be controlled by adjusting the ink application—using less ink results in finer cracks, while a thicker application produces larger, more pronounced cracks. For the best results, it is recommended to apply a medium to thick layer to achieve optimal texture and depth.

The formulation is engineered for easy application and works well with both manual and automatic screen printing techniques. Global AQ Auto Crack Base 9110 is ideal for creating unique, distressed, or vintage-style designs on various textile substrates. Its durability ensures that the cracking effect remains intact even after multiple washes, maintaining the aesthetic appeal of the printed fabric.

**IDEAL FABRIC**  
100 % cotton or polyester blends

**STORAGE**  
In cool dry and properly closed  
(18°C to 32°C)

**ADDITIVES**  
If require AquaFix additives

**CLEAN UP**  
Wash off screen using water and  
mild detergent

**CURING**  
160°C for 3 minutes

**MESH**  
80 to 120 mesh  
use micron capillary fil for bir cracks

**APPLICATION**  
Should be use without any  
modification

**SQUEEGEE & STENCIL**  
Solvent & Water resistant emulsion  
65 to 70 duro meter beveled edge

The Global Inc.(India)

4/18 3rd cross street,(opp.Vinayagar Temple),  
Karuvampalayam,  
Tirupur -641 604

+91 424342677,4324677

www.theglobalchem.com

sales@tglibm.com  
info@tglibm.com